

Zaina-4

- 
- Wooden blinds
 - Vertical blinds
 - Roller blinds
 - Magic screen
 - Motor system
- 

Drop Awning for Outdoor

INTELLIGENT SUNSHADING ZIPPER TRAK ROLLERS BLINDS

**MR-ZT03 / Z705
OPEN GUIDE TRACKING SYSTEM**

• ACCESSORIES LIST

1. MR-ZT03-101 • Front box
2. MR-ZT03-102 • Rear box
3. MR-ZT03-301 • Installation bracket
4. MR-ZT03-301 • Aluminum tube
5. MR-ZT03-103 • Tubular motor
6. MR-ZT03-401 • Motor accessories
7. MR-ZT03-303 • Fixxtor
8. MR-ZT03-302 • Side cap
9. MR-ZT03-410 • Mr-banma logo
10. TSL-2 • Fabric
11. MR-ZT03-101 • Wire rope
12. MR-ZT03-501 • Bottom stick
13. MR-ZT03-301 • Fixing stick
14. MR-ZT03-602 • Counterweight bar
15. MR-ZT03-104 • Bottom rail
16. MR-ZT03-303 • Screw
17. MR-ZT03-306 • Wall terminal
18. MR-ZT03-403 • Wall terminal cover
19. MR-ZT03-403 • Floor terminal

• High strength aluminum roller cassette with electrostatic outdoor powder coating

• Same curve design for bottom rail and cassette.

• Exquisite high strength components which perfectly match the blind.

• Mount method / wall mounting / floor mounting.

• MOUNTING

MAX :
3T03
width 300 cm a height 320 cm
2705
width 500 cm a height 320 cm
MIN
width 100 cm a Height 100 cm

• The location of the installation must be installed at both ends to ensure the balance of the force

Installation-Top view

outside

APPLICATION SCENARIO

WINDOWS

BALCONY

FRENCH WINDOWS

LEISURE PAVILION

• Widely used in : villas, five-star hotels, car 45 shop, exhibition hall, outdoor courtyard and other places.

Drop Awning for Outdoor

INTELLIGENT SUNSHADING ZIPPER TRAK ROLLERS BLINDS



Composition	: 38% Fiberglass + 62% PVC
Weight per m2	: 495 g/m2 ± 5%
Finished Width	: 320 cm.
Openness Factor	: 3%
Roll Length	: 30 m Thickness
Thickness	: 0.62 mm. ± 5%
Color Fastness	: 8 Grade (SGS) Fire Resistance : B1
Breaking Strength	: Warp 2000 N / 5 cm.
	: Weft 1800 N / 5 cm.



Zip Blinds

กันแดดแนวตั้ง

OPENNESS FACTOR 5%



OPENNESS FACTOR 1%



Wind resistance



Water proof



Anti UV



Mosquito proof



Fire resistance



Wind resistance up to 130 km/h

SPECIFICATION

Series	Tube Size	Max Width	Max Height	Min Size
W85 series Manual available	60 mm	2500 mm	2500 mm	Width Size : 1000mm Height Size : 1000mm
W105 series Manual available	70 mm	4000 mm	3500 mm	Width Size : 1000mm Height Size : 1500mm
W136 series	95 mm	6000 mm W: 6000mm, Max height: 3000mm	6000 mm H: 6000mm, Max width: 3000mm	Width Size : 4000mm Height Size : 3500mm



Removable motor bracket,
more convenient to replace the motor



Special zip track system
wind resistant : 12 scale



Separate tracks and concealed screws,
much easier assemble and disassemble



Inner tracks with polymer wearing
layer to be more durable



Bottom rail with inner strips to
make it more closed and quiet



EVA sponge strip makes the fabric
flat well

